



v-LANE A2B 2MPX@60 fps Multifunctional ANPR 250 Km/h

- Telecamera singola testa infrarossi + colori (bispettrale) , Copertura di 1 corsia
- Lettura targhe fino a 250 km/h in free-run
- Illuminatore IR integrato a led stroboscopici
- Risoluzione 2 Mpixel (contesto + OCR)
- Libreria OCR on board con 41 nazioni Europa, 13 Asia, 6 Africa, 5 Sud America e targhe speciali quali Rimorchi, Kemler ADR, Kemler ADR Empty, Tram
- Classificazione diurna dei veicoli per tipologia in 11 + 1 (Macchine, Camion, Camion con rimorchio, Motoveicoli, Motocicli, Ciclomotori, Bus, Mini van, Big van, Cassonati, Caravan, sconosciuto)
- Classificazione notturna dei veicoli per tipologia in 4 classi +1 (camion, bus, macchine, motoveicoli e sconosciuto)
- Classificazione diurna dei veicoli per colore in 11 classi + 1 (nero, bianco, grigio, rosso, blu, giallo, verde, arancio, rosa, viola, ciano, sconosciuto)
- Classificazione brand del veicolo (circa 100 brand supportati)
- Classificazione modello dei veicoli in transito ripresa posteriore (circa 400 modelli supportati)
- Algoritmi di AID di varco per il controllo del traffico (veicolo fermo, veicolo contromano, traffico lento, coda)
- Funzione stima della velocità di transito
- Liste Black & White
- ONVIF Profilo S
- Funzione NVR locale per storage registrazione continua dello streaming video e creazione di micro filmati su transito
- Compatibile con la piattaforma di supervisione generale v-SUITE di Vigilate, Accessibile via Cloud
- Libreria OCR più volte validata UNI 10772:2016 Classe A



CARATTERISTICHE:

Analisi e riconoscimento: v-LANE A2B is the 2Mpixels intelligent camera able to control and manage all the problems of a road gate both for safety aspects and for aspects relating to traffic control. v-LANE A2B detects 60 images per second within which it analyzes, identifies and validates the license plates of the vehicles present. This result obtained through the use of sophisticated software makes it possible to read the license plate of vehicles in transit at speeds of up to 250 km/h in free-run mode (without an external trigger device).

Dati: Dati ed immagini possono essere memorizzati direttamente in locale, inviati al sistema di supervisione del cliente o inviati alla piattaforma di supervisione v-SUITE. Il dispositivo dispone di protocolli di trasmissione FTP, XML-RPC (su HTTPS) e seriale. Software Libreria di Optical Character Recognition (OCR) completa di 41 nazioni Europa, 13 Asia, 6 Africa, 5 Sud America e targhe speciali quali Rimorchi, Kemler ADR, Kemler ADR Empty, Tram (Polizia, Esercito, Ambulanze, Protezione civile...).

Classificazione: La camera è dotata di un software di classificazione video in grado di riconoscere le tipologie di veicolo con 11 + 1 classi tra cui (Macchine, Camion, Camion con rimorchio, Motoveicoli, Motocicli, Ciclomotori, Bus, Mini van, Big van, Cassonati, Caravan, sconosciuto); inoltre è in grado d'individuare il colore dominante tra una gamma di 11 colori + 1 (nero, bianco, grigio, rosso, blu, giallo, verde, arancio, rosa, viola, ciano, sconosciuto). v-Lane è dotata di algoritmi di AID di varco per il controllo del traffico (veicolo fermo, veicolo contromano, traffico lento, coda)

Sicurezza dei dati: La memorizzazione e la trasmissione dei dati generati dal prodotto, avvengono mediante protocolli altamente affidabili e sicuri, garantendo il massimo livello d'inviolabilità e privacy. Vigilate rispetta le normative più restrittive sulla sicurezza del dato quali la ISO27001:2022 .

Esempi di applicazioni: Controllo accessi parcheggi pubblici e privati, Controllo accessi zone residenziali e commerciali, Piste di accesso a porti, aeroporti, stazioni etc...



v-LANE A2B 2MPX@60 fps Multifunctional ANPR 250 Km/h

SPECIFICHE TECNICHE:

Sensor (OCR + COLOR):	2 MP (1920 x 1080) CMOS COLOR + IR (bispectral) global shutter sensor
Frame rate:	Up to 60 fps
Optics:	Standard varifocal lens, 8-50 mm
Integrated IR illuminator:	n. 8 LED IR (CLASS 1M CEI EN 69825-1 ED. 4, 850 nm IR LED)
Processor:	Quad-core + HW video encoder unit + Neural coprocessor
Memory:	16 GB e-MMC Flash
RAM:	4 GB
S.O.:	Linux
Storage Disk:	HD SSD 128 GB (up to 2 TB)
I/O:	N. 2 input opto-isolated N. 1 output relè N. 1 fast output strobo 12-24 VDC N. 1 output open-collector 12-24 VDC
Ports:	N.1 USB port N.1 RS-485 port N.1 10/100/1000 Mbps Ethernet port
Operating mode:	- continuously acquisition (free-run) - on request (by SW trigger or HW trigger) Both modes can draw on the two local lists that can be configured locally or by remote synchronization with the FTP server
Real-time diagnostics:	- CPU temperature - Mainboard temperature - IR illumination module operation - Lighting module current peaks - Capture status of physically connected sensors - Input current level (power port) - Input voltage level (power port) - Camera tilt angle - Internal humidity level - CPU consumption - RAM consumption - Storage disks status - Utilization of the 4 physical cores (CPU monitoring) - Check status of operational threads - Monitoring of analysis times and operating status of active algorithms Generation of any alarms (local and possibly remote) in the face of anomalies detected
Supported sending protocols:	- TCP (in binary, XML, string formats) - TCP Milestone - FTP (imgs + text data in *.txt/*.csv) - RPC-XML over HTTP / HTTPS (BASIC or EXTENDED message) - Custom Protocol (message configurable via template and sendable by HTTP POST / HTTPS POST /TCP protocols) - Serial (on RS 485 port) - Wiegand (need to install SC20 converter)

V-260424-0954-UPD

Vigilate S.r.l.

Via Napoleonica, 6 - 25086 Rezzato BS Tel. +39 030 8081000 | Fax +39 030 8081019 | www.vigilatevision.com | info@vigilatevision.com
 Cap. Soc. € 10.000,00 I.V. | C.F. / P.IVA : IT 01598660056 - SDI: W7YVJK9



Dasa-Rägister



v-LANE A2B 2MPX@60 fps Multifunctional ANPR 250 Km/h

	<ul style="list-style-type: none"> - Xentinel message (over HTTP) - v-SUITE message (over HTTP / HTTPS)
Supported communication protocols:	TCP/IP, UDP, HTTP, HTTPS, FTP, FTPS, RTP/RTSP, OpenVPN, ONVIF (S-profile), NTP, SNMP
Data protection:	<ul style="list-style-type: none"> - possibility to activate the management of the web configurator by HTTPS connection - FTPS encryption on TLS/SSL protocol - AES-256-ECB encryption for data and images saved locally and/or sent via the supported protocols - image hash using SHA-512 algorithm and possible encryption of the signature itself using AES-256-ECB - totally GDPR compliant storage management with periodic deletion of the history - cockpit masking function (in case of front detection of vehicles) in order to ensure respect for privacy - possibility to connect the camera inside an openVPN with certificate installed directly on board - advanced management of the firewall on the machine with the possibility of disabling access to the local servers present on the machine (FTP server, ONVIF server, SNMP server, service ports)
Supported power supply:	24VDC (2,5 A) or +12VDC (5 A) or UPoE 60W class 6
Consumption:	12W typically
Dimensions:	450 x 140 x 150 mm
Weight:	2,6 Kg
Operating temperature:	- 30°; +60°
Humidity:	up to 90%
Protection:	IP67 - class IK10 (on request)
OCR library:	Certified high reliability, the library has been validated several times by UNI 10772
Classification algorithms:	The percentages of correct classification depend on compliance with the installation geometry but are above 90% regardless of the external environmental conditions
AID algorithm:	The instantaneous speed estimation by video analysis and consequently the AID algorithm with the various supported features are highly reliable as demonstrated by numerous field tests in the presence of approved systems for speed estimation for sanctioning purposes.
Regulations complied with:	EN 55032/2015, EN 55035/2017, EN 50561-1/2013, EN 62368-1 (EN 62368-1/2014+A11/2017), EN 60068-2-14/Nb 2011-11, EN 60068-2-78/2013-11, EN 62471/2010, EN 60529/1991+A1/2000+A2/2013, UE Regulation 2016/679 (GDPR)